Technical Specification Sheet



Product code: 85.330

Carton Sealing Machine

Side Belt Drive with flap closer and guards

Automate your packing line and reduce labour costs with an automatic carton sealing machine.

Automatic carton sealing machines are the key to increasing warehouse productivity. These machines also reduce the risk of back injury and provide a more reliable and neater carton tape sealing solution, replacing the need to manually tape up the cartons by hand.

This automated carton sealer, also known as a box taping machine, is operated by two side belts driving a carton through top and bottom tape dispensing rollers. These rollers apply pressure-sensitive adhesive machine tape to the box as it travels on the conveyor through the machine, sealing the flaps closed. Once the box exits the sealing unit, the next box is immediately ready to be fed through.

The Omni Automatic machine has a conveyor speed of 19 meters per minute and can be integrated into a driven automatic conveyor. It can work in conjunction with other machines in the production line such as carton erectors, pallet wrappers, and heat shrink machines. This model machine can be used to tape any carton that has a width of 150mm to 480mm and a height of 120mm to 480mm.

Specifications	Result
Machine size	L1650mm×W980mm×H(table height+890mm)
Table height	550mm~750mm (adjustable)
Conveyor speed	19 metres per minute
Power supply	1P, AC110V/220V, 50Hz/60Hz, 400W
Carton dimensions	L(200~550)mm, W(150~480)mm, H(120~480)mm
Net weight	280kg
Tape type	Adhesive tape (48~72)mm (kraft or BOPP tape)

Features:

- Fast & efficient.
- Sturdy steel construction.
- Industrial wheels for easy mobility.
- Easy to use control panel.
- Service friendly machine, easy access to all required parts.

enquiries@omnigroup.com.au

1300 764 963

HQ 15-23 Logistics Street, Keilor Park, VIC 3042

4